



Thinfit Collection™

THINFIT MODELS

As audio installations have become more common, speakers are being placed in all types of environments. Sometimes, the requisite depth behind the drywall for a traditional in-wall or in-ceiling speaker does not exist. Our Thinfit Collection™ allows for speakers to be mounted in many of these locations.



TF37



TFIW37



TF34



TF64DT

EASY FIT

Requiring less than 1 1/2" (36mm), these speakers can be easily installed in all but the most restrictive spaces.



1 7/16" (36mm)

SPECIFICATIONS

MODEL	TF37	TFIW37	TF34	TF64DT
PART	STF3700	STFIW3700	STF3400	STF2T640
Woofer	Quad 3" (76mm) Fiberglass	Quad 3" (76mm) Fiberglass	3 1/2" IMG	6 1/2" IMG
Tweeter	3/4" (20mm) Silk DPSD™	3/4" (20mm) Silk DPSD™	3/4" Aluminum	Dual 3/4" Aluminum
Frequency Response	100Hz-20kHz	100Hz-20kHz	50Hz-20kHz	50Hz-20kHz
Power RMS	60 Watts	60 Watts	30 Watts	30 Watts
Power Peak	100 Watts	100 Watts	100 Watts	100 Watts
Impedance	4 ohm	4 ohm	8 ohm	8 ohm
Diameter	9 5/8" (244mm)	5 1/2" x 17 1/2" x 1 7/16" (140 x 440 x 36mm)	9 5/8" (244mm)	9 5/8" (244mm)
Cutout Diameter	8 3/4" (222mm)	4 5/8" x 16 7/16" (118 x 418mm)	8 3/4" (222mm)	8 3/4" (222mm)
Grille Diameter	10" (254mm)	6 x 18" (152 x 452mm)	10" (254mm)	10" (254mm)
Mounting Depth	1 7/16" (36mm)	1 7/16" (36mm)	2 3/4" (70mm)	2 3/4" (70mm)
MSRP	\$345/EA	\$350/EA	\$290/EA	\$230/EA
DEALER	\$125/EA	\$130/EA	\$100/EA	\$80/EA

