



CustomSound

CS1000 Universal Loudspeaker	CS500 Universal Loudspeaker
45-23,000Hz 59-20,000Hz	65-23,000Hz 65-10,000Hz
40Hz	50Hz
86dB 88dB	85dB 87dB
8 Ohms 6 Ohms	8 Ohms 6 Ohms
20 - 150 Watts 150 Watts	20 - 120 Watts 120 Watts
1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet
6 1/2" (165mm) Clay/Ceramic filled Polypropylene Cone, Rubber Surround	5 1/4" (135mm) Clay/Ceramic filled Polypropylene Cone, Rubber Surround
2,200Hz, LR4	1,800Hz, LR4
0.3 cu ft (8.5L)	0.2 cu ft (5L)
Bass Reflex	Sealed
9 1/4 x 12 1/4 x 11 3/4" 235 x 310 x 296mm	7 5/8 x 10 1/2 x 8" 192 x 266 x 203mm
10lbs (4.5kg)/each 24lbs (11kg)/pair	5.7lbs (2.59kg)/each 16.5lbs (7.5kg)/pair
Black or White	Black or White

All specifications are subject to change without notice. Non-metric measurements are approximate. PSB Speakers will not assume any liability for errors in this brochure which may result in errors being made by retailers, custom installers, cabinet makers or other end users based on information contained in this document. PSB Speakers reserves the right to change specifications or features without notice. © 2011 PSB Speakers, a division of Lenbrook Industries Limited. PSB is a registered trademark of Lenbrook Industries Limited. All rights reserved. No part of this publication may be reproduced, stored or transmitted in any form whatsoever without the written permission of PSB Speakers. Printed April 2011 * Please allow minimum 3" / 75mm for cord clearance.