

SubSeries 350 Powered Subwoofer



The new SubSeries 350 Subwoofer with its 12" woofer offers extensive musicality and high-powered bass impact. The "green" and highly efficient discrete MOSFET amplifier uses less energy to produce more power while reducing standby power to an industry low. Its "smart bass" limiting circuitry prevents the woofer and amplifier from being overdriven with any input level. The SubSeries 350 features trickle down fit and finish from the SubSeries 450. Its deceptively compact sealed cube design, housed in an elegant high gloss black cabinet, makes for easy placement in the home. Capable of 300 watts of continuous power and dynamic peaks of 900 watts, the SubSeries 350 offers a winning combination of power, high impact bass, and musicality.

About Subwoofers

All speakers play an important role in your home theatre system, but the performance of your subwoofer can greatly affect the overall performance of your system. Think of a subwoofer as a vital component to your system, adding excitement to your music or theatre experience and understanding that not all subwoofers are created equal. With our audiophile heritage here at PSB Speakers, our engineers place a particular emphasis on the overall musicality of our subwoofers. Distinct attention is given to their ability to seamlessly match our high-quality speakers under the most demanding music and film score passages. Equally important is the subwoofer's ability to sustain powerful lower frequencies for extended periods of time. PSB Speakers offers a full range of subwoofers to meet the needs of our discerning customers.

- Finish: High Gloss Black
- 300W Continuous, 400W Dynamic Peak Power
- 12" Woofer, polypropylene cone
- Class D, Discrete MOSFET
- Rear mounted Volume, Crossover and Phase Controls
- Low Level Inputs/Low Level Outputs with 80Hz High Pass
- High Level Inputs/Outputs (Full Range)
- LFE Input/Output
- Sealed Cabinet
- Auto On/Off, Standby Bypass switch
- <0.5W Standby Power Consumption
- USB Power jack for RT100 wireless accessory
- Vibration absorbing feet
- Gross Dimensions:
15 3/8" x 15 3/8" x 15 3/8" (WxHxD)
(391 x 391 x 391mm)

SubSeries 350 Powered Subwoofer



| | |
|---|--|
| FREQUENCY RANGE | |
| On Axis @ 0° ± 3dB LF Cutoff -10dB | 25-150Hz 20Hz |
| INPUT IMPEDANCE | |
| Low Level High Level | 9k Ohms 400 Ohms |
| AMPLIFIER POWER | |
| Continuous Dynamic Peak Design LED Indicator | 300W 400W Class D RED > STANDBY, GREEN > ON |
| ACOUSTIC DESIGN | |
| Woofers | 12" (305mm) Polypropylene Cone |
| Crossover Frequency | Variable 50-350Hz (LFE) |
| Design Type | Sealed |
| CONSTRUCTION – SLEEVE ONLY | |
| Front Baffle Grille | MDF ABS |
| SIZE (W x H x D) | |
| Net Dimensions | 15.375 x 15.375 x 15.375" (390 x 390 x 395mm) |
| Gross Dimensions including grille, feet, knobs and terminals | 15.75 x 16 x 16.25" (400 x 405 x 410mm) |
| Shipping | 21.75 x 21.75 x 21.25" (550 x 550 x 538mm) |
| WEIGHT | |
| Shipping | 51lb (22.8kg)/each |
| FINISH | |
| | High Gloss Black |
| FEATURES | |
| Controls | <ul style="list-style-type: none"> Volume Control (Amplifier mount) Variable Crossover Control (Amplifier mount) 180° Phase Control (Amplifier mount) Standby Control Switch (Amplifier mount) |
| Connections | <ul style="list-style-type: none"> Gold Plated RCA Low/Line Level Stereo Input & Outputs High Level Inputs & Outputs Gold-plated 5-way Binding Posts USB Power Output (5V, 500mA) |
| Other | <ul style="list-style-type: none"> Vibration Absorbing Feet Selectable Mains Voltage Detachable 8 foot IEC C17 Mains Power Cord (Both NA & EU power cords supplied) Auto On/Stand-by |
| Energy Star Compliance | <ul style="list-style-type: none"> 0.5W STANDBY |
| NOTES | |
| | Fuse is not user accessible |

REAL SOUND for REAL PEOPLE
www.PSBspeakers.com