8K Ultra High Speed

SLIMWIRE MAX (48G) HDMI CABLE



No other HDMI cable will give you better picture and sound from your 8K TV setup. Supporting the full HDMI 2.1 (a/b) 48Gbps max data rate end-to-end.

Capable of carrying the most premium ultra high speed 8K 60 4:4:4 content, along with all HDR formats (10 & 12-bit), Dolby Vision, HDR10+ and HLG.

Features

| HDMI® 2.1 compliant (a/b) | | | | |
|---|--|--|--|--|
| HDCP 2.3 compliant | | | | |
| Uncompressed 8K@60fps 4:4:4, 4K@120fps and 10K@30fps | | | | |
| Officially Certified for 48G | | | | |
| Static/dynamic HDR, HDR10 & Dolby Vision | | | | |
| 21:9 screen ratio support | | | | |
| Enhanced Audio Return Channel (eARC) | | | | |
| Ethernet Channel & CEC supported | | | | |
| DTS Master, DTS:X, Dolby TrueHD, & Dolby Atmos Audio | | | | |
| Supports: VRR, ALLM, QMS, QFT | | | | |
| Small precision-manufactured compact aluminium headshell assembly | | | | |
| 24K Gold Plated HDMI male connectors | | | | |

Specification

| Available Sizes | 0.5, 1, 1.5, 2, 3, 4, metres |
|---------------------------|---|
| Thickness | 30 AWG (5m 28 AWG) 99.9% high purity oxygen-free copper conductor |
| Colour | Carbonite |
| Conductors | OFHC (Oxygen-Free High-Conductivity) copper |
| Insulation (inner jacket) | High-density polyethylene (HD-PE) |
| Layers 1 & 2 Shielding | 100% Aluminium Foil |
| Layer 3 Shielding | 95% Al+My braid |
| Insulation (outer jacket) | PVC |
| Contacts | Gold plated |
| Configuration | 19+1 Pin |
| Guarantee | 5-year guarantee |

LENGTHS & SKUS

| 0.5m | 1.55.917.001.1 | 3.0m | 1.55.917.005.1 |
|------|----------------|------|----------------|
| 1.0m | 1.55.917.002.1 | 4.0m | 1.55.917.006.1 |
| 1.5m | 1.55.917.003.1 | | |
| 2.0m | 1 55 917 004 1 | | |













