



Technical Data Sheet

PRO⁴ 48Gbps Active Optical HDMI Cable







1kgf / 10N (nominal)



The Kordz PRO4 Active Optical HDMI Cable is the professional grade solution for uncompressed 8K/10K HDMI connectivity over ultra long distances. Supporting full 48Gbps data rates, it delivers seamless performance from 7.5m up to 100m, with minimal latency and no external power required. Its lightweight ABS connector assembly with goldplated HDMI connector ensure secure, reliable connections, while the robust 4.7mm cable diameter and 20kg pullforce rating provide exceptional durability. Individually tested and DPL Labs certified for true 48Gbps performance, the

- PRO4 AOC HDMI Cable is the professional's choice for demanding AV installations. Supports uncompressed 48Gbps for 8K/10K video transmission up to 100m
- No external power required for ease of installation
- Lightweight ABS connector assembly with 1kg retention force

- Inner metallic shell for component protection and EMI shielding
 4.7mm cable diameter with 20kg pull rating for durability
 Individually tested and DPL Labs certified for guaranteed performance
- · Fire-rated to UL CMG standards for fire safety
- · Backed by a 2-year warranty
- Eco-friendly packaging









Connector Retention Force











		Ų		
Technical Specifications		Reference Standards:		
Performance		7.5m to 100.0m Active Optical		
HDMI Certification		High Speed with Ethernet		
Supported HDMI Data Rate		DPL Labs certified 48Gbps (12Gbps per lane)		
Other HDMI Features		eARC not supported		
Construction				
Primary Channels (TMDS/FRL)		OM3 (50/125) optical fibre		
4C + HEAC Pairs	Conductors	Tinned Copper, 30-26 AWG		
	Insulation	Foamed PE / HDPE		
Overall Shielding		AL / Mylar		
Cable Jacket Material		UL CMG fire-rated PVC composite materials		
HDMI Connector Shell		Premium gauge folded steel, 1µ" 24K Gold-plated		
HDMI Connector Pins		Solid OFC, 18µ" 24K Gold-plated		
Active Optical Technology		Directional, In-shell Optical Light Engine		
HDMI Back-shell		ABS front shell with PVC injection moulded boot and strain relief		
Mechanical				
Cable Diameter		4.7mm / 0.19in Ø		
Mounting Depth		7.5m-20m: 70.1mm / 2.76in 25m-100m: 84.8mm / 3.34in		
Cable Bend Radius		37.6mm		

Part No	Length	Box Size	Carton Size	Master Ctn Qty
K2651G -0750-CH	7.5m 24.6ft	270 (L) x 270 (W) x 28 (H) mm	558(L) x 298(W) x 310(H)mm	20 pcs
K2651G -1000-CH	10.0m 32.8ft			
K2651G -1250-CH	12.5m 41ft			
K2651G -1500-CH	15.0m 49.2ft			
K2651G -2000-CH	20.0m 65.6ft	270 (L) x 270 (W) x 48 (H) mm		12 pcs
K2651G -2500-CH	25.0m 82ft			
K2651G -3000-CH	30.0m 98.4ft			
K2651G -5000-CH	50.0m 164ft	270 (L) x 270 (W) x 70 (H) mm		8 pcs
K2651G -7500-CH	75.0m 246.1ft			
K2651G -100M-CH	100.0m 328.1ft			

Kordz products are sold with a limited warranty as outlined at: www.kordz.com
@2025 Kordz International. All rights reserved. Kordz Connectivity.Assured & Kordz range logos are trademarks or registered trademarks of Kordz International in Hong Kong and in other countries. All other trademarks are the property of their respective owners.