



Marquee Collection™



A no-compromise loudspeaker and amplification solution for extreme home theater installations.



M1500SUB



M2500IC

FLOOR STANDING & IN-CEILING

Triggering the most primal emotional responses, the M1500 Subwoofer establishes a sonic foundation upon which the entire Marquee system is built. Timbre matched to the rest of the Marquee loudspeakers, the M2500 shares the same dynamic response and life like nuance in an in-ceiling format. It is a perfect choice for side, rear and Atmos® channels when the architectural design demands.



ROCK SOLID AMPLIFICATION

Built to deliver the necessary horsepower to drive the M1500 Sub, the SubA500 pulls no punches. Internal digital processing and 500 Watts of Class-D amplification will drive the 15" pro-style woofer to levels that will hit you in the chest like a freight train.



SUBA500

SPECIFICATIONS

MODEL	M1500SUB	SUBA500
PART	M1500SUB	AMPSUB1X500
Woofers	Front firing, 15" coated paper woofer with accordion surround	
Channels		1
Inputs		Line Level for LFE or amp preout Speaker Level
Feature		Analog Loop for Daisy Chain Option
Frequency Response	25Hz – 150Hz	
Power RMS	200 Watts	500 Watts Class D Power
Power Peak	1000 Watts	
Impedance	6 ohm	Stable to 4 Ohm
Dimensions		1 ¾ x 17 x 10 ⅝" (45 x 435 x 264mm)
Dimensions w/Feet	27 ¾" x 18 ⅛" x 21 ²¹⁄₃₂" (705 x 460 x 550 mm)	

MODEL	M2500IC
PART	M2500IC
Woofers	10" Coated Paper Woofer
Midrange	3 ½" Coated Paper
Tweeter	¾" Titanium MMP™
Frequency Response	70Hz – 20kHz
Power RMS	50 Watts
Power Peak	150 Watts
Impedance	4 ohm
Diameter	11 ¼" (286 mm)
Grille Diameter	11 ¾" (298 mm)
Cut-Out Diameter	10 ⅜" (264 mm)
Mounting Depth	6 ¼" (158 mm)

