

VRX70-18G 4K HDBaseT™ Receiver



The VRX70-18G HDMI® 2.0 4K60Hz 4:4:4 (18Gbps) HDCP2.2 HDBaseT™ Receiver pairs perfectly with the VX44-18G-Kit* and the VX88-18G and offers market-leading features and outstanding value, including Color Space Conversion (CSC) technology. The product extends HDMI®, Bi-directional IR, and is powered by the matrix up to lengths of 70m (4K 40m). The VRX70-18G HDMI® 2.0 4K60Hz 4:4:4 (18Gbps) HDCP2.2 HDBaseT™ Receiver pairs perfectly with the VX44-18G-Kit* and the VX88-18G and offers market-leading features and outstanding value, including Color Space Conversion (CSC) technology. The product extends HDMI®, Bi-directional IR, and is powered by the matrix up to lengths of 70m (4K 40m).

* The VX44-18G-Kit comes with 4 x VXR70-18G

Compatible Products



VX44-18G
4 x 4 4K HDBaseT™ Matrix Switcher



VX88-18G
8 x 8 4K HDBaseT™ Matrix Switcher

Key Features

- Advanced HDBaseT™ technology enables distribution of video and audio over a single CAT cable
- Advanced color Space Conversion (CSC) supports HDMI® 2.0 18Gbps specification including HDR
- Supports all industry standard video resolutions including VGA-WUXGA and 480i-4K and all known HDMI® audio formats including Dolby TrueHD®, Dolby Atmos®, Dolby Digital Plus® and DTS-HD Master Audio® transmission
- HDMI® re-clocking to help solve HDMI® HDCP, compatibility and handshaking issues
- IR pass-through to compatible HDBaseT™ devices
- Supports bi-directional PoC (Power over Cable) from VX88-18G
- HDCP 2.2 support

Included in the Box







VRX70-18G (1), Mounting Kit (1)

Specifications

Video Input Connectors..... 1 x HDBaseT™ RJ45 Connector
 Video Output Connectors 1 x HDMI® Type A, 19-pin, female
 Audio Input Connectors 1 x Toslink (S/PDIF)
 Audio Output Connectors..... 1 x Toslink (S/PDIF), 1 x 3.5mm L/R Analog Audio
 HDBaseT™ Transmission 1080p@50/60Hz ≤ 131ft (70m)
 Distance 3840 x 2160 @50/60Hz 4:4:4 ≤ 229ft (40m)
 Max. Bandwidth..... 18Gbps
 RS-232 serial port 1 x 3-Pin Phoenix Connector
 IR Input ports 1 x 3.5mm Stereo Jack
 IR Output ports..... 1 x 3.5mm Mono Jack
 Mounting Kit..... Included
 Dimensions (WxDxH)..... 5.5" x 3.3" x .7"
 140mm x 84mm x 18mm
 Dimensions (WxDxH)..... 5.5" x 3.5" x .7"
 (including connectors) 140mm x 88mm x 18mm
 Shipping Weight..... 1.3lbs. (0.6kg)
 Operating Temperature 32°F to 104°F (-5°C to +55°C)
 Storage Temperature -4°F to 140°F (-25°C to +70°C)
 Power Supply 1x 12V/1A DC, Screw Connector
 Warranty Three Years (Parts & Labor)

All features and specifications subject to change without notice

State-of-the-Art Video Technology

- 
HDBaseT™
 No bottleneck with the latest HDBaseT™ 18Gbps standard that provides the highest possible bandwidth that currently exists.
- 
4K UHD
 Enjoy stunning picture quality with 4K UHD resolution.
- 
2160p 60Hz 4:4:4
 Eliminate blurred fast motions in action movies. 4K resolution paired with 60Hz refresh rate provides a crystal clear and crisp picture quality.
- 
229ft 70m
 Long Distance
 Go beyond the distance limitations of HDMI® cables. Video can be transmitted over a Cat cable up to 229ft/70m.
- 
HDCP 2.2
 Be fully compliant with the latest copy protection algorithms to avoid black screens when connecting an HDMI® source
- 
PoH
 Power over HDBaseT™
 Get rid of extra power supplies for HDBaseT™ receivers. Remote devices can be powered over the HDBaseT cable.

Example Schematic

